

DISPLAYS



FIELD DISPLAY 57 MM

casing model name 575F5
dimensions 310 X 138 X 96 mm
digit size 57 mm
number of digits 5 digits
display color Red LED
number of inputs/outputs 1/2
inputs 2000 series inputs
outputs (optional) 0/4...20 mA, 0...5/10 V
settings By keys inside casing
alarms (optional) 2...4 relays, 240 VAC, 2A
serial signal RS232, RS485, Nokeval SCL
sensor supply 24 VDC, max. 150 mA
protection class IP65
power supply 85...240 VAC, 12...32 VDC / 24 VAC
note Includes 2000-series input card



FIELD DISPLAY 100 MM

casing model name FD100
dimensions 4 digits: 477 X 191 X 100 mm
 6 digits: 659 X 191 X 100 mm
digit size 100 mm
number of digits 4/6 digits
display color Red LED
number of inputs/outputs 1/2
inputs 2000 series inputs
outputs (optional) 0/4...20 mA, 0...5/10 V
settings By keys inside casing
alarms (optional) 2...4 relays, 240 VAC, 2A
serial signal RS232, RS485, Nokeval SCL
sensor supply 24 VDC, max. 150 mA
protection class IP65
power supply 85...240 VAC, 12...32 VDC / 24 VAC
note Includes 2000-series input card



FIELD DISPLAY 200 MM

casing model name FD200
dimensions 4 digits: 713 X 260 X 120 mm
 6 digits: 1013 X 260 X 120 mm
digit size 200 mm
number of digits 4/6 digits
display color Red LED
number of inputs/outputs 1/2
inputs 2000 series inputs
outputs (optional) 0/4...20 mA, 0...5/10 V
settings By keys inside casing
alarms (optional) 2...4 relays, 240 VAC, 2A
serial signal RS232, RS485, Nokeval SCL
sensor supply 24 VDC, max. 150 mA
protection class IP65
power supply 85...240 VAC, 12...32 VDC / 24 VAC
note Includes 2000-series input card